

性能参数

型号	流量Q		扬程H (m)	转速 r/m in	功率P KW
	m ³ /h	L/s			
15-80	1.5	0.42	8	2800	0.18
20-110	2.5	0.69	15	2800	0.37
20-160	2.5	0.69	32	2900	0.75
25-110	4	1.11	15	2900	0.55
25-125	4	1.11	20	2900	0.75
25-160	4	1.11	32	2900	1.5
25-160A	3.7	1.03	28	2900	1.1
32-100(I)	6.3	1.75	12.5	2900	0.75
32-125(I)	6.3	1.75	20	2900	1.1
32-160(I)	6.3	1.75	32	2900	2.2
32-200(I)	6.3	1.75	50	2900	4.0
40-100	6.3	1.75	12.5	2900	0.75
40-125	6.3	1.75	20	2900	1.1
40-125A	5.6	1.56	16	2900	0.75
40-160	6.3	1.75	32	2900	2.2
40-160A	5.9	1.64	28	2900	1.5
40-160B	5.2	1.53	24	2900	1.1
40-200	6.3	1.75	50	2900	4.0
40-200A	5.9	1.64	44	2900	3.0
40-200B	5.5	1.53	38	2900	2.2
40-250	6.3	1.75	80	2900	7.5
40-250A	5.9	1.64	70	2900	5.5
40-250B	5.5	1.53	60	2900	4.0
40-100(I)	12.5	3.47	12.5	2900	1.1
40-100(IA)	11.2	3.11	10	2900	0.75
40-125(I)	12.5	3.47	20	2900	1.5
40-125(IA)	11.2	3.11	17.2	2900	1.1
40-160(I)	12.5	3.47	32	2900	3.0
40-160(IA)	11.7	3.25	28	2900	2.2
40-160(IB)	10.5	2.92	22.5	2900	1.5
40-200(I)	12.5	3.47	50	2900	5.5
40-200(IA)	11.7	3.25	44.5	2900	4.0
40-200(IB)	10.5	2.92	35	2900	3.0
40-250(I)	12.5	3.47	80	2900	11.0
40-250(IA)	11.7	3.25	70	2900	7.5
40-250(IB)	10.5	3.0	60	2900	7.5
50-100	12.5	3.47	12.5	2900	1.1
50-100A	11.2	3.11	10	2900	0.75
50-125	12.5	3.47	20	2900	1.5
50-125A	11.2	3.11	17.2	2900	1.1
50-160	12.5	3.47	32	2900	3.0
50-160A	11.7	3.25	28	2900	2.2
50-160B	10.5	2.92	22.5	2900	1.5
50-200	12.5	3.47	50	2900	5.5
50-200A	11.7	3.25	44.5	2900	4.0
50-200B	10.5	2.92	35	2900	3.0
50-250	12.5	3.47	80	2900	11.0
50-250A	11.7	3.25	70	2900	7.5
50-250B	10.8	3.0	60	2900	7.5
50-100(I)	25	6.94	12.5	2900	1.5
50-100(IA)	22.4	6.22	10	2900	1.1

型号	流量Q		扬程H (m)	转速 r/m in	功率P KW
	m ³ /h	L/s			
50-125(I)	25	6.94	20	2900	3.0
50-125(IA)	22.4	6.22	16	2900	2.2
50-160(I)	25	6.94	32	2900	4.0
50-160(IA)	23.4	6.5	28	2900	4.0
50-160(IB)	21.6	6.0	24	2900	3.0
50-200(I)	25	6.94	50	2900	7.5
50-200(IA)	23.4	6.5	44	2900	7.5
50-200(IB)	21.6	6.0	37	2900	5.5
50-250(I)	25	6.94	80	2900	15
50-250(IA)	23.4	6.5	70	2900	11
50-250(IB)	21.6	6.0	60	2900	11
50-315(I)	25	6.94	125	2900	30
50-315(IA)	23.4	6.5	110	2900	22
50-315(IB)	21.6	6.0	93	2900	18.5
65-100	25	6.94	12.5	2900	1.5
65-100A	22.4	6.22	10	2900	1.1
65-125	25	6.94	20	2900	3.0
65-125A	22.4	6.22	16	2900	2.2
65-160	25	6.64	32	2900	4.0
65-160A	23.4	6.5	28	2900	4.0
65-160B	21.6	6.0	24	2900	3.0
65-200	25	6.94	50	2900	7.5
65-200A	23.4	6.5	44	2900	7.5
65-200B	21.6	6.0	37	2900	5.5
65-250	25	6.94	80	2900	15
65-250A	23.4	6.5	70	2900	11
65-250B	21.6	6.0	60	2900	11
65-315	25	6.94	125	2900	30
65-315A	23.4	6.5	110	2900	22
65-315B	21.6	6.0	93	2900	18.5
65-100(I)	50	13.9	12.5	2900	3.0
65-100(IA)	44.8	12.4	10	2900	2.0
65-125(I)	50	13.9	20	2900	5.5
65-125(IA)	44.8	12.4	16	2900	4.0
65-160(I)	50	13.9	32	2900	7.5
65-160(IA)	46.8	13.0	28	2900	7.5
65-160(IB)	43.2	12.0	24	2900	5.5
65-200(I)	50	13.9	50	2900	15
65-200(IA)	46.8	13.0	44	2900	11
65-200(IB)	43	11.9	37	2900	7.5
65-250(I)	50	13.9	80	2900	22
65-250(IA)	46.8	13.0	70	2900	18.5
65-250(IB)	43	11.9	60	2900	15
65-315(I)	50	13.9	125	2900	37
65-315(IA)	45.8	12.7	105	2900	30
65-315(IB)	43	11.9	93	2900	30
80-100	50	13.9	12.5	2900	3.0
80-100A	44.8	12.4	10	2900	2.2
80-125	50	13.9	20	2900	5.5
80-125A	44.8	12.4	16	2900	4.0
80-160	50	13.9	32	2900	7.5

备注：以上 RG、YG、HG、SW性能参数相同

性能参数

型号	流量Q		扬程H (m)	转速 r/min	功率P KW
	m ³ /h	L/s			
80-160A	46.8	13.0	28	2900	7.5
80-160B	43.2	12.0	24	2900	5.5
80-200	50	13.9	50	2900	15
80-200A	46.08	13.0	44	2900	11
80-200B	43	11.9	37	2900	7.5
80-250	50	13.9	80	2900	22
80-250A	46.8	13.0	70	2900	18.5
80-250B	43	11.9	60	2900	15.0
80-315	50	13.9	125	2900	37.0
80-315A	45.8	12.7	105	2900	30.0
80-315B	43	11.9	93	2900	30.0
80-100(I)	100	27.8	12.5	2900	5.5
80-100(I)A	89	24.7	10	2900	4.0
80-125(I)	100	27.8	20	2900	11.0
80-125(I)A	89	24.7	16	2900	7.5
80-160(I)	100	27.8	32	2900	15.0
80-160(I)A	93.5	26	28	2900	11.0
80-160(I)B	86.4	24	24	2900	11.0
80-200(I)	100	27.8	50	2900	22.0
80-200(I)A	93.5	26	44	2900	18.5
80-200(I)B	86.4	24	37	2900	15.0
80-250(I)	100	27.8	80	2900	37.0
80-250(I)A	93.5	26	70	2900	30.0
80-250(I)B	86.4	24	60	2900	30.0
80-350(I)	100	27.8	125	2900	75.0
80-350(I)A	93.5	26	110	2900	55.0
80-350(I)B	86.4	24	93	2900	45.0
100-100	100	27.8	12.5	2900	5.5
100-100A	89	24.7	10	2900	4.0
100-125	100	27.8	20	2900	11.0
100-125A	89	24.7	16	2900	11.0
100-160	100	27.8	32	2900	15.0
100-160A	93.5	26	28	2900	11.0
100-160B	86.4	24	24	2900	11.0
100-200	100	27.8	50	2900	22.0
100-200A	93.5	26	44	2900	18.5
100-200B	86.4	24	37	2900	15
100-250	100	27.8	80	2900	37
100-250A	93.5	26	70	2900	30
100-250B	86.4	24	60	2900	30
100-315	100	27.8	125	2900	75
100-315A	93.5	26	110	2900	55
100-315B	86.4	24	93	2900	45
100-100(I)	160	44.4	12.5	2900	11.0
100-125(I)	160	44.4	20	2900	15.0
100-125(I)A	143	39.7	16	2900	11.0
100-160(I)	160	44.4	32	2900	22
100-160(I)A	150	41.7	28	2900	18.5
100-200(I)	160	44.4	50	2900	37
100-200(I)A	150	41.7	44	2900	30
100-200(I)B	138	38.3	37	2900	22

型号	流量Q		扬程H (m)	转速 r/min	功率P KW
	m ³ /h	L/s			
100-250(I)	160	44.4	80	2900	55
100-250(I)A	150	41.7	70	2900	45
100-250(I)B	138	38.3	60	2900	37
125-160	200	55.5	32	2900	30
125-160A	187	51.9	28	2900	22
125-200	200	55.5	50	2900	45
125-200A	187	51.9	44	2900	37
125-200B	172	47.8	37	2900	30
125-250	200	55.5	80	2900	75
125-250A	187	51.9	70	2900	55
125-250B	172	47.8	60	2900	45
125-315	200	55.5	125	2900	90
125-315A	187	51.9	110	2900	75
125-315B	172	47.8	93	2900	75
150-250	200	55.5	80	2900	18.5
150-250A	187	51.9	70	2900	15
150-250B	172	47.8	60	2900	11
150-315	200	55.5	125	2900	30
150-315A	187	51.9	110	2900	22
150-315B	172	47.8	93	2900	18.5
40-125(I)	6.3	1.75	5	1450	1.1
40-160(I)	6.3	1.75	8	1450	0.55
40-160(I)A	5.5	1.53	6	1450	0.37
40-200(I)	6.3	1.75	12.5	1450	4
40-200(I)A	5.8	1.61	11.0	1450	3
40-250(I)	6.3	1.75	20	1450	2.2
40-250(I)A	5.8	1.61	17.0	1450	1.1
40-125	6.3	1.75	5	1450	0.55
50-160	6.3	1.75	8	1450	0.55
50-160A	5.5	1.53	6	1450	0.37
50-200	6.3	1.75	12.5	1450	0.75
50-200A	5.8	1.61	11.0	1450	0.55
50-250	6.3	1.75	20	1450	1.5
50-250A	5.8	1.61	17.0	1450	1.1
50-125(I)	12.5	3.47	5	1450	0.55
50-160(I)	12.5	3.47	8	1450	0.75
50-160(I)A	11	3.1	6	1450	0.37
50-200(I)	12.5	3.47	12.5	1450	1.1
50-200(I)A	11.2	3.11	10	1450	0.75
50-250(I)	12.5	3.47	20	1450	2.2
50-250(I)A	11.7	3.25	17.5	1450	1.5
50-250(I)B	10	2.78	13	1450	1.1
50-315(I)	12.5	3.47	32	1450	4.0
50-315(I)A	11.7	3.25	28	1450	3.0
50-315(I)B	10	2.78	21	1450	3.0
65-125	12.5	3.47	5	1450	0.55
65-160	12.5	3.47	8	1450	0.75
65-160A	11	3.1	6	1450	0.37
65-200	12.5	3.47	12.5	1450	1.1
65-200A	11.2	3.11	10	1450	0.75
65-250	12.5	3.47	20	1450	2.2

备注：以上 RG、YG、HG、SW性能参数相同

性能参数

型号	流量Q		扬程H (m)	转速 r/min	功率P KW
	m ³ /h	L/s			
65-250A	11.7	3.25	17.5	1450	1.5
65-250B	10	2.78	13	1450	1.1
65-315	12.5	3.47	32	1450	4.0
65-315A	11.7	3.25	28	1450	3.0
65-315B	10	2.78	21	1450	3.0
65-125(I)	25	6.94	5	1450	0.75
65-160(I)	25	6.94	8	1450	1.5
65-160(I)A	22	6.1	6	1450	1.1
65-200(I)	25	6.94	12.5	1450	2.2
65-200(I)A	23.3	6.47	11	1450	1.5
65-250(I)	25	6.94	20	1450	3.0
65-250(I)A	22.2	6.17	15.8	1450	2.2
65-250(I)B	20	5.56	12.8	1450	1.5
65-315(I)	25	6.94	32	1450	5.5
65-315(I)A	22.5	6.25	26	1450	4.0
65-315(I)B	20	5.56	21.0	1450	3.0
80-125	25	6.94	5	1450	0.75
80-160	25	6.94	8	1450	1.5
80-160A	22	6.1	6	1450	1.1
80-200	25	6.94	12.5	1450	2.2
80-200A	23.3	6.47	11	1450	1.5
80-250	25	6.94	20	1450	3.0
80-250A	22.2	6.17	15.8	1450	2.2
80-250B	20	5.56	12.8	1450	1.5
80-315	25	6.94	32	1450	5.5
80-315A	22.5	6.25	26	1450	4.0
80-315B	20	5.56	21	1450	3.0
80-125(I)	50	13.9	5	1450	1.5
80-160(I)	50	13.9	8	1450	2.2
80-160(I)A	46	12.8	6	1450	1.5
80-200(I)	50	13.9	12.5	1450	4.0
80-200(I)A	44.7	12.4	10	1450	3.0
80-250(I)	50	13.9	20	1450	5.5
80-250(I)A	46	12.8	17.0	1450	4.0
80-250(I)B	40.5	11.25	13.0	1450	3.0
80-315(I)	50	13.9	2	1450	11.0
80-315(I)A	46	12.8	27.9	1450	7.5
80-315(I)B	40.5	11.25	21	1450	5.5
100-125	50	13.9	5	1450	1.5
100-160	50	13.9	8	1450	2.2
100-160A	46	12.8	6	1450	1.5
100-200	50	13.9	12.5	1450	4.0
100-200A	44.7	12.4	10	1450	3.0
100-250	50	13.9	20	1450	5.5
100-250A	46	12.8	17.0	1450	4.0
100-250B	40.5	11.25	13	1450	3.0
100-315	50	13.9	32	1450	11.0
100-315A	46	12.8	27.9	1450	7.5
100-315B	40.5	11.25	21	1450	5.5
100-125(I)	80	22.2	5	1450	2.2
100-160(I)	80	22.2	8	1450	3.0

型号	流量Q		扬程H (m)	转速 r/min	功率P KW
	m ³ /h	L/s			
100-160(I)A	72	20	6.5	1450	2.2
100-200(I)	80	22.2	12.5	1450	5.5
100-200(I)A	72	20	10	1450	4.0
100-250(I)	80	22.2	20	1450	11.0
100-250(I)A	75	20.8	17.5	1450	7.5
100-250(I)B	69	19.2	15	1450	5.5
100-315(I)	80	22.2	32	1450	15.0
100-315(I)A	75	20.8	27.5	1450	11.0
100-315(I)B	70	19.4	24	1450	11.0
100-400(I)	80	22.2	50	1450	22
100-400(I)A	75	20.8	44	1450	18.5
100-400(I)B	70	19.4	38	1450	15.0
125-125	100	27.8	5	1450	2.2
125-160	100	27.8	8	1450	4.0
125-160A	87	24.2	6	1450	4.0
125-200	100	27.8	12.5	1450	7.5
125-200A	89	24.7	10	1450	5.5
125-250	100	27.8	20	1450	11.0
125-250A	93.3	25.9	17.5	1450	7.5
125-250B	87	24.2	15	1450	7.5
125-315	100	27.8	32	1450	15.0
125-315A	91	25.3	27	1450	11.0
125-315B	87	24.2	24	1450	11.0
125-400	100	27.8	50	1450	30
125-400A	94	26.1	44	1450	22
125-400B	87	24.2	37.5	1450	18.5
125-200(I)	160	44.4	12.5	1450	11.0
125-200(I)A	143	39.7	10	1450	7.5
125-250(I)	160	44.4	20	1450	15.0
125-250(I)A	147	40.8	17	1450	11.0
125-250(I)B	134	37.2	14	1450	7.5
125-215(I)	160	44.4	32	1450	22
125-215(I)A	150	41.7	28	1450	18.5
125-215(I)B	138	38.3	24	1450	15.0
125-400(I)	160	44.4	50	1450	37
125-400(I)A	150	41.7	44	1450	30
125-400(I)B	138	38.3	38	1450	30
150-200	160	44.4	12.5	1450	11.0
150-200A	143	39.7	10	1450	7.5
150-250	160	44.4	20	1450	15.0
150-250A	147	40.8	17	1450	11.0
150-250B	134	37.2	14	1450	7.5
150-315	160	44.4	32	1450	22
150-315A	150	41.7	28	1450	18.5
150-315B	138	38.3	24	1450	15.0
150-400	160	44.4	50	1450	37
150-400A	150	41.7	44	1450	30
150-400B	138	38.3	38	1450	30
150-200(I)	200	55.6	12.5	1450	15.0
150-200(I)A	179	49.7	10	1450	11.0
150-250(I)	200	55.6	20	1450	18.5

备注：以上 RG、YG、HG、SW性能参数相同

性能参数

型号	流量Q		扬程H (m)	转速 r/m in	功率P KW
	m ³ /h	L/s			
150-250 (I)A	187	51.9	17.5	1450	15.0
150-250 (I)B	173	48.9	14	1450	11.0
150-315 (I)	200	55.6	32	1450	30
150-315 (I)A	187	51.9	28	1450	22
150-315 (I)B	173	48.1	24	1450	18.5
150-400 (I)	200	55.6	50	1450	45
150-400 (I)A	187	51.9	44	1450	37
150-400 (I)B	173	48.1	37.5	1450	30
200-200	200	55.6	12.5	1450	15.0
200-200A	179	49.7	10	1450	11.0
200-250	200	55.6	20	1450	18.5
200-250A	187	51.9	17.5	1450	15.0
200-250B	173	48.9	14	1450	11.0
200-315	200	55.6	32	1450	30
200-315A	187	51.9	28	1450	22
200-315B	173	48.1	24	1450	18.5
200-400	200	55.6	50	1450	45
200-400A	187	51.9	44	1450	37
200-400B	173	48.1	37.5	1450	30
200-200 (I)	400	111.1	12.5	1450	22
200-200 (I)A	358	99.4	10	1450	18.5
200-250 (I)	400	111.1	20	1450	30
200-250 (I)A	358	99.4	16	1450	22
200-250 (I)B	322	89.4	13	1450	18.5
200-315 (I)	400	111.1	32	1450	55
200-315 (I)A	374	103.9	28	1450	45
200-315 (I)B	346	96.1	24	1450	37
200-400 (I)	400	111.1	50	1450	90
200-400 (I)A	374	103.9	44	1450	75
200-400 (I)B	347	96.1	38	1450	55
200-400 (I)C	320	88.9	32	1450	45.0
200-510 (I)	400	111.1	82	1450	132
200-510 (I)A	374	103.9	70	1450	110
200-510 (I)B	346	96.1	60	1450	90.0
200-270	400	111.1	80	1450	132
200-270A	352	97.8	70	1450	110
200-270B	320	88.9	56	1450	75.0
200-330	400	111.1	128	1450	200
220-330A	351	97.8	113	1450	200
220-330B	220	80.5	96	1450	132
200-380	320	88.8	128	1450	200
200-250	550	152.8	20	1450	45
250-250A	490	136.1	16	1450	37
250-315	550	152.8	32	1450	75
250-315A	515	143	28	1450	55
250-315B	476	132.2	24	1450	45
250-400	550	152.8	50	1450	110
250-400A	515	143	44	1450	90
250-400B	476	132.2	37.5	1450	75
250-480	550	152.8	70	1450	160
250-480A	500	131.9	60	1450	132
250-500	600	167	82	1450	220

型号	流量Q		扬程H (m)	转速 r/m in	功率P KW
	m ³ /h	L/s			
250-500A	550	152.8	74	1450	200
250-400	720	200	50	1450	132
250-400A	600	180.6	44	1450	110
300-460	720	200	65	1450	250
300-460A	666	185	55	1450	200
300-460B	614	170.6	45	1450	132
300-235 (I)	1080	300	40	1450	220
300-235 (I)A	965	268.1	32	1450	160
300-235	720	200	18	970	55
300-235A	657	182.5	15	970	45
300-300	720	200	28	970	75
300-300A	666	185	24	970	75
300-300B	623	173.1	21	970	55
300-380	720	200	44	970	132
300-380A	666	185	38	970	110
300-380B	623	173.1	33	970	90
300-330 (I)A	920	88.8	18	970	90
300-380 (I)	1080	300	42	970	200
300-380 (I)A	920	256	37	970	160
300-500 (I)	1080	300	72	970	355
300-500 (I)A	920	256	66	970	315
300-250	800	222.2	20	970	75
300-250A	715	198.6	16	970	55
300-315	800	222.2	32	970	90
350-315A	748	207.8	28	970	75
350-315B	692	192.2	24	970	75
350-400	800	222.2	50	970	160
350-400A	750	208.3	44	970	132
350-400B	697	193.6	38	970	110
350-460	1200	333.3	50	970	250
350-460A	1080	300	44	970	200
350-380	1500	416	42	970	280
350-380A	1340	372	36	970	250
400-400	1080	300	12.5	970	55
400-400A	966	268.3	10	970	45
400-500	1080	300	20	970	90
400-500A	996	276.7	17	970	75
400-500B	935	259.7	15	970	55
400-625	1080	300	32	970	132
400-625A	996	276.7	27	970	110
400-625B	935	259.7	24	970	90
400-400	1200	333.3	12.5	970	75
400-400A	1073	298.1	10	970	55
500-470	2000	555.5	20	970	160
500-470A	1800	500	17	970	132
500-500	1200	333.3	20	970	110
500-500A	1106	307.2	17	970	90
500-500B	1040	288.9	15	970	75
500-625	1200	333.3	32	970	160
500-625A	1106	307.2	27	970	132
500-625B	1040	288.9	24	970	110

备注：以上 RG、YG、HG、SW性能参数相同